

**Zimmer**  
MedizinSysteme



Cryo**Mini**

Zimmer

# CryoMini



## **CryoMini**

Cold Air Skin Cooling -

- Standby mode - permits instant user operation
- Immediate cooling available for patient treatment
- 9 fan speeds ensure optimum air-flow selection

**Enhanced patient comfort**

**Cost efficient – no consumables**

**Compact – small x-base**

**Lightweight – easily transportable**

The CryoMini cold air system has been created to meet the needs of aesthetic procedures with shorter durations.

## The Skin Cooling System for Laser and IPL Treatments



### Patient Satisfaction

Simultaneous application of cold air in conjunction with laser and IPL treatments leads to a distinct reduction in pain and may reduce thermal tissue damage. Various studies have indicated that longer treatment sessions may be possible due to increased patient comfort. Additionally, cold air has been favored as a successful method for providing local anaesthesia prior to injections.

### Versatility

A major advantage of the *CryoMini's* non-contact skin cooling is that skin can be cooled before, during and after most treatments, without interfering with the laser application or requiring additional preparation time.

### Easy Operation

The touch screen ensures ease of operations. One button start up. Nine fan speeds available to accommodate patient's requirements.

Treatment time adjusted by pressing one button.

### Quick and Efficient Application

The cold air can be more selectively directed onto localized treatment areas by utilizing the laser handpiece adapter. An optional support arm is available to gently hold and guide the air tube to provide the operator with hands-free operation. *CryoMini* requires only normal room air, which is filtered and chilled to  $-10^{\circ}\text{C}$ . There are no consumables or additional costs. The customized glass plate provides a compact location for various accessories, IPL laser systems, or smoke evacuator.



## Technical Data

Power supply Versions	230 V / 50 Hz-60 Hz 115 V / 60 Hz
Power input max.	1000 VA
Stand-by function	100 W/h
Protection according to IEC 601-1	Class I, Type B
MDD / MPG	Class IIa
Treatment tube length	180 cm
Housing dimensions	H 650 mm / W 335 mm / L 600 mm
Weight	35,5 kg
Air flow	9 levels, ~ 1300 l / min

## Options



Articulating arm



Adapter



D33 Treatment hose

Zimmer MedizinSysteme GmbH  
Junkersstraße 9  
D-89231 Neu-Ulm  
Tel. +49 7 31. 97 61-291  
Fax +49 7 31. 97 61-299  
export@zimmer.de  
www.zimmer.de